



Power Sentry Fluorescent Battery Packs Lamp Compatibility Guide

Lamp Type	Wattage	PS300QD	PSQ500QD	PS600QD	PS1400QD	PSL400	PSL550	PSL600	PS600C	PS3000	PS48	PSDL1	PSDL2	PSDL3
Lumens		300	450-550	600-700	1100-1400	350-450	390-700	900-1325	600-700	1500-3000	*	500-950	350-650	580-1070
24"-48" T5	14-28			1	1		1	1		1				
24"-48" T5HO	25-54			1	1		1	1		1				
U-Lamp T8	16-32	1	1	1,2	1,2	1				1	1,2			
24"-48" T8	17-32	1	1	1,2	1,2	1		1	3	1	1,2			
48"-60" T8	32-40						1	1			1			
48" T8HO	44						1	1						
Circline T9	20-40	1		1	1					1,2	1			
U-Lamp T12	34-40	1	1	1,2	1,2	1				1,2	1,2			
24"-48" T12	20-40	1	1	1,2	1,2	1			3	1,2	1,2			
60"-96" T12	50-75			11	1					1	1			
24"-48" T12HO	35-60			1	1					1	1			
60"-96" T12HO	70-110			1	1					1	1			
24"-48" T12VHO	74-115			1	1					1	1			
60"-96" T12VHO	135-215			1	1					1	1			
PL Twin-Tube (2-Pin)	9-13										1		1	
PL Quad-Tube (2-Pin)	13-26										1	1,4		
PL Twin-Tube (4-Pin)	9-13				1						1,2			1
PL Quad-Tube (4-Pin)	13-26				1,2					1	1,2			1,2
Triple-Tube (4-Pin)	18-32				1,2	1				1	1			1,2
Triple-Tube (4-Pin)	42				1						1			1
Long Compact (4-Pin)	18-40	1	1	1		1				1	1,2			
Long Compact (4-Pin)	36-55						1	1			1,2			

NOTES:

* Based on the lumen output of the lamp; provides full light output.
 1. One-lamp emergency operation for 1, 2, 3 or 4-lamp ballasts.
 2. Two-Lamp emergency operation for 2, 2 or 4-lamp ballasts.

3. One-lamp, 2 hour emergency operation for 2, 3 or 4-lamp ballasts.
 4. 2 LP option required for 2-lamp emergency operation in fixtures with two or more lamps.